

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 August 2004 (12.08.2004)

PCT

(10) International Publication Number  
**WO 2004/067376 A2**

(51) International Patent Classification<sup>7</sup>: **B63H**  
(21) International Application Number:  
PCT/US2004/002750  
(22) International Filing Date: 29 January 2004 (29.01.2004)  
(25) Filing Language: English  
(26) Publication Language: English  
(30) Priority Data:  
10/354,353 30 January 2003 (30.01.2003) US

(71) Applicant (for all designated States except US): AUBURN  
UNIVERSITY [US/US]; Office of Technology Transfer,  
309 Samford Hall, Auburn University, AL 36849-5176  
(US).

(71) Applicant and

(72) Inventor: SMITH, Joseph, A. [US/US]; P.O. Box 16951,  
Mobile, AL 36616 (US).

(74) Agent: SMITH, Joseph, A.; P.O. Box 16951, Mobile, AL  
36616 (US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-  
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,  
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: MARINE HYDRO LIFT FLAPS AND METHODS OF USING SAME



(57) Abstract: An apparatus for improving performance of a vessel, wherein the vessel has a hull 100 having a bottom 103, a bow 100a and a stern 100b. In one embodiment, the apparatus has at least one flap 101, wherein the flap 101 has a forward edge 101a, a rear edge 101b, and a body portion defined therebetween the forward edge 101a and the rear edge 101b, the body portion having an exterior surface 101c and an opposite, interior surface 101d, and is movably mounted to the bottom 103 of the hull 100 at the forward edge 101a such that each flap 101 can be moved between a first position and a second position apart from the first position. The apparatus also has means for moving the flap 101 between the first position and the second position.



**Published:**

— without international search report and to be republished  
upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*